




MARK: _


PROJECT: _____

DATE:



DIMENSION DATA

Size	Α	В	С	Wheel Dia.	Ship Wt.
ERV-1500	40-1/2	49-1/4	54-1/4	28	604
ERV-2500	50	52	52	36	722
ERV-3500	59	60-1/2	64-1/2	42	990
ERV-4500	64-1/2	66-1/2	69-1/2	48	1111
ERV-5500	71	66-1/2	69-1/2	54	1235
ERV-7000	76-1/2	80	79-1/2	60	1609
ERV-8500	83	80	79-1/2	66	1734
ERV-10000	90	84-1/2	100	72	2817



ŰŲL


ACCESSORIES

- 13-1/2" high roof curbs
- Duct Adapters

1.

2

- Duct Flanges for Discharge Openings 3.
- Duct Flange for Intake Openings 4 5
- Intake Weatherhood
- Tiered Intake Weatherhood
- Motorized Intake Dampers
- 11
- Insulated Motorized Intake Dampers 12.
- Ductwork



Energy Recovery Ventilator

Internal Belt Drive

- 14. Dampers for Field Mounting in Supply Ductwork
- Hinged Access Doors 15
- Quarter Turn Latches 16.
- Double Wall Construction 17
- Sensible only Wheels 18.
- Adjustable Purge Section 19
- 20. Ceiling Mount Isolators
- 21 Field Installed Disconnect Switches
- 22. **Dirty Filter Sensor**
- 23 Rotation Sensor
- Economizer Mode with Temperature 24. Sensor
- 25. Economizer Mode with Enthalpy Sensor
- 26. On/Off Frost Control
- 27. Exhaust Only Frost Control
- 28. Preheat Frost Control

ALL DIMENSIONS IN INCHES. WEIGHTS IN LBS., LESS MOTOR.

STANDARD CONSTRUCTION FEATURES:

Energy recovery wheel constructed of fluted synthetic media containing water selective molecular sieve desiccant - Cassette assembly slides out for easy access and consists of energy recovery wheel, drive motor, and drive components - Removable access doors provide access to all internal componenets - Ventilator cabinet consisting of a minimum 18 gauge galvanized steel housing mounted to a minimum 16 gauge galvanized steel base - Cabinet internally lined with 1" thick, 3 lb. density, FSK insulation - Two DWDI forward curved steel blowers mounted on vibration isolators - Blower wheel bearings rated at 200,000 hours average life - Blower wheels are factory adjusted to specified RPM - Standard size 2" thick, MERV 8 filters in supply and exhaust air streams - All electrical components pre-wired for single point power connection - Interlock disconnect on hinged control panel door

		FAN INFORMATION							MOTOR INFORMATION							
CATALOG	SUPPLY			EXHAUST			SUP	EXH				TVDE	ACCESSORIES			
	NUMBER	CFM	EFF	SP	RPM	CFM	EFF	SP	RPM	HP	HP	VOLTS	ΠZ	РП		

- 6. Exhaust Weatherhood 7 8. Lorenized Finish Gravity Intake Dampers 9
 - 10.
 - Low Leakage Motorized Intake Dampers
 - Dampers for Field Mounting in Exhaust 13